

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



FM CASE 3031


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : <b>F16D 65/847, 55/40</b>		A1	(11) International Publication Number: <b>WO 00/09909</b>
			(43) International Publication Date: 24 February 2000 (24.02.00)
(21) International Application Number: PCT/GB99/02533 (22) International Filing Date: 2 August 1999 (02.08.99) (30) Priority Data: 9817741.3 15 August 1998 (15.08.98) GB (71) Applicant (for all designated States except US): FEDERAL-MOGUL TECHNOLOGY LIMITED [GB/GB]; Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): BUNKER, Kenneth, James [GB/GB]; 39A Mill Road, Rearsby, Leicester LE7 4YN (GB). (74) Agent: DRURY, Peter, Lawrence; T & N Limited, Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published With international search report.	

(54) Title: DISC BRAKE SYSTEM

(57) Abstract

A disc brake system (10) comprises a disc (12, 14), and a hub (16) which is arranged to rotate about an axis (18) thereof. The hub (16) comprises a mounting portion (16d) which is generally in the shape of a hollow cylinder. The system (10) also comprises mounting means (20, 22) by which the disc (12, 14) is mounted on the external surface of said mounting portion (16d) for rotation with said hub (16) as a unit about said axis (18) and the disc (12, 14) can perform axial sliding movement on said hub. Said hub (16) carries vanes (62) arranged so that, during rotation of the hub (16) about said axis (18), the vanes act to force air into the interior of said mounting portion (16d). Said mounting portion (16d) has openings (60) therethrough arranged so that air forced into the interior of the mounting portion (16d) passes through said openings and flows over said disc (12, 14).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

### DISC BRAKE SYSTEM

This invention is concerned with a disc brake system, for example for a wheel of a vehicle.

A conventional disc brake system comprises a disc brake, and a hub which provides a mounting for a wheel. The hub is mounted, eg on a suspension link of a vehicle, for rotation about a central axis of the hub. The disc brake comprises a disc which is fixedly mounted on the hub for rotation therewith. The brake also comprises friction material pads arranged on opposite sides of the disc, and a piston and cylinder assembly operable to urge the pads into engagement with the disc, to brake the hub and hence the wheel. Conventionally, the piston and cylinder assembly is slidably mounted and a caliper bridging an edge of the disc is fixed to a cylinder of the assembly. One friction pad is acted on directly by the piston and cylinder assembly while the other pad is mounted on the caliper on the opposite side of the disc. Operation of the assembly presses one pad against the disc and causes sliding movement of the cylinder of the assembly and of the caliper to bring the other pad into engagement with the disc, thereby applying a braking force to the disc and hence to the hub. Such a disc brake generates considerable quantities of heat which limits the materials which can be used and, eg because of thermal expansion effects, can adversely affect the performance of the brake. In order to remove some of the heat generated, it is known to provide cooling passages through the disc through which air is drawn by centrifugal force (see eg WO 97/21042 and GB 2 001 716 A). However, this solution complicates the

manufacture of the disc and is not available when the disc is thin (as is desirable to save weight).

In WO 98/25804, a disc brake system is described in which two discs are mounted on the same hub. The use of two discs reduces the heat generated at each disc but makes it even more desirable for the discs to be thin. As described in WO 98/25804, each disc is mounted on the hub by mounting means which is arranged so that the hub and the discs rotate about the central axis of the hub as a unit but the discs can perform axial sliding movement on the hub. The system also comprises a piston and cylinder assembly having its cylinder fixed relative to a suspension link of a vehicle, the cylinder being integrally formed with the link. The system also comprises a caliper fixed relative to the cylinder, the caliper providing supports for friction material pads of the system, including pads between the two discs. The pad furthest from the assembly is fixed to the caliper but the remaining pads are slidably mounted thereon. When the piston and cylinder assembly is operated, a pad operated upon by the assembly and the pads between the discs slide on the caliper, and the discs slide on the hub until each disc is engaged on both sides by a pad.

In WO 98/25804, the hub has a mounting portion which is generally in the shape of a hollow cylinder, and the mounting means mounts the discs on the external surface of the mounting portion. The mounting means described comprises a plurality of axially-extending grooves formed in the hub and teeth projecting from the discs into the grooves, each tooth being a sliding fit in one of said grooves.

It is an object of the present invention to provide improved cooling for a disc of a disc brake system in which the disc can perform axial sliding movement on a hub.

The invention provides a disc brake system comprising a disc, and a hub which is arranged to rotate about an axis thereof, the hub comprising a mounting portion which is generally in the shape of a hollow cylinder, the system also comprising mounting means by which the disc is mounted on the external surface of said mounting portion for rotation with said hub as a unit about said axis and so that the disc can perform axial sliding movement on said hub, characterised in that said hub carries vanes arranged so that, during rotation of the hub about said axis, the vanes act to force air into the interior of said mounting portion, and in that said mounting portion has openings therethrough arranged so that air forced into the interior of the mounting portion passes through said openings and flows over said disc.

In a disc brake system according to the invention, the disc is cooled by the air in a simple manner which allows thin discs to be used. The present invention is applicable to a disc brake system of the type described in WO 98/25804 but is also applicable to other disc brake systems having a disc which is axially movable on a hub.

In a disc brake system according to the invention, said mounting means may comprise a plurality of axially-extending grooves formed in the hub and teeth projecting from the disc into the grooves, each tooth being a sliding fit in one of said grooves, said openings being formed in portions of the hub which are between the grooves. The grooves may be in groups as disclosed in WO 98/25804. Other forms of mounting means are also possible, for example the roller arrangement disclosed in WO 98/26192.

Where the hub has grooves as afore-mentioned, a system according to the invention may also comprise a plurality of leaf springs mounted on said hub on portions thereof which are between said grooves, the leaf springs acting to apply

radial force between the disc and the hub (such leaf springs are disclosed in WO 98/25804 and act to control the movement of the disc on the hub). In this case, said springs may have openings therethrough which correspond to said openings in the hub, thereby allowing passage for the air.

Conveniently, said vanes are mounted on a phonic wheel of an anti-lock braking system mounted on said hub.

In order to accommodate the movement of the disc on the hub, said openings in the hub may be in the form of slits which are elongated in the axial direction.

There now follows a detailed description, to be read with reference to the accompanying drawings, of two disc brake systems which are illustrative of the invention.

In the drawings:

Figure 1 is a vertical cross-sectional view taken through the first illustrative disc brake system;

Figure 2 is a view similar to Figure 1 but with parts omitted of the second illustrative disc brake system;

Figure 3 is an elevational view of a phonic wheel of the second illustrative system; and

Figure 4 is a transverse cross-sectional view taken through the phonic wheel shown in Figure 3.

The first illustrative disc brake system 10 shown in Figure 1 comprises a disc 12, a further disc 14 and a hub 16, on which a wheel (not shown) can be mounted. The discs 12 and 14 and the hub 16 are arranged to rotate about a central axis 18 of the hub 16.

The hub 16 comprises an internally splined hollow inner cylindrical portion 16a which is arranged to receive a drive shaft (not shown) which drives the wheel. The hub

16 also comprises an external flange 16b at one end of the portion 16a. This flange 16b has bolt holes 16c through which the wheel (not shown) can be bolted to the flange 16b in a conventional manner. The flange 16b also serves to connect the portion 16a to a mounting portion 16d of the hub 16. The mounting portion 16d is generally in the shape of a hollow cylinder open at one end, closed by the portion 16b at the other end, and having an external surface 16e.

The discs 12 and 14 are identical to one another, being in the form of generally-annular relatively-thin cast iron or steel plates. The two discs 12 and 14 are mounted by means of mounting means of the brake 10 on the cylindrical outer surface 16e of the hub portion 16d so that the two discs 12 and 14 rotate as a unit with the hub 16 about the axis 18 and the discs 12 and 14 can perform axial sliding movement on said hub 16. The mounting means comprises grooves 20 which are formed in the outer cylindrical surface 16e of the portion 16d of the hub 16 and teeth 22 which project inwardly from each of the discs 12 and 14. The teeth 22 enter the grooves 20 and are a sliding fit therein. Between the grooves 20, the outer surface 16e of the hub portion 16d is machined to be accurately cylindrical about the axis 18. The inner surface of each disc 12 and 14, between the teeth 22, is also machined to be accurately cylindrical about the axis 18 and a close fit over the cylindrical portions of the outer surface of the hub portion 16d. The close fit of the discs 12 and 14 on the hub 16 reduces the possibility of the discs 12 and 14 tipping.

The brake system 10 also comprises four friction material pads 26 which are arranged with two of the pads 26 on opposite sides of each of the discs 12 and 14. The pads 26 are for braking the discs 12 and 14 by engaging side surfaces of the discs. The friction pads 26 are secured to three backing plates 28, one backing plate 28a being



between the discs 12 and 14 and the others being on opposite sides of the discs 12 and 14 to the plate 28a. The median plate 28a has pads 26 secured to both of its faces. When the brakes are applied, a movable outer pad 26 is moved until the four pads 26 and the discs 12 and 14 are all in contact with one another, the discs 12 and 14 and the plate 28a sliding axially to accommodate this movement.

The brake system 10 also comprises resilient means in the form of leaf springs 32 of the type described in WO 98/25804. The leaf springs 32 are mounted on the hub 16 and engaging the discs 12 and 14 so that the springs 32 apply force radially between each of the discs 12 and 14 and the hub 16. The leaf springs 32 are distributed circumferentially around the hub 16, each being mounted on the surface 16e between the grooves 20.

The system 10 also comprises an operating mechanism in the form of a piston and cylinder assembly comprising a piston 50 and a cylinder 52, the cylinder 52 is fixed relative to the axis 18 being integral with a suspension link (not shown) of the vehicle as disclosed in WO 98/25804. The assembly 50, 52 is operable to move a first of the pads 26 into contact with the disc 12 and to cause relative movement between the assembly 50, 52 and the disc 12 to bring the other pad 26 associated with the disc 12 into contact with the disc 12, so that the pads 26 apply a braking force to the disc 12. Specifically, a caliper 54 is mounted on the cylinder 52 and bridges the edges of both discs 12 and 14. The furthest pad 26 from the cylinder 52 has its support plate 28 fixedly mounted on the caliper 54 while the support plates 28 of the remaining pads 26 are slidable on the caliper 54. When the piston 50 is moved outwardly from the cylinder 52 by hydraulic fluid under pressure, it directly presses the support plate 28 of the nearest pad 26 so that the plate 28 slides on the bridge

54. The nearest pad 26 presses the disc 12 so that it slides on the hub 16. The disc 12, in turn, presses on the pad 28 on the opposite side thereof causing the support plate 28a to slide on the caliper 54. The movement of the plate 28a causes the pad 26 on the plate 28a which faces the disc 14 to contact the disc 14. The disc 14 slides on the hub 16 until it contacts the pad 26 on the plate 28 which is fixed to the bridge 54. The brake 10 is now "on" with the discs 12 and 14 both engaged on both sides by one of the pads 26. The pads 26, therefore, apply braking forces to the discs 12 and 14 which forces are transferred to the hub 16.

In order to cool the discs 12 and 14, said hub 16 carries vanes 62 arranged so that, during rotation of the hub 16 about said axis 18, the vanes 62 act to force air into the interior of said mounting portion 16d. Specifically, said vanes 62 project from the annular surface of portion 16d at the opposite end thereof to the flange portion 16b. In this case, the vanes 62 are cast integrally with the hub 16 but they may be attached instead. The vanes 62 are preferably as shown in Figures 2 to 4 but may be curved and/or angled as desired.

Said mounting portion 16d of the hub 16 also has openings 60 therethrough arranged so that, during rotation of the hub 16 and the discs 12 and 14, air forced into the interior of the mounting portion 16d passes through said openings and flows over said discs 12 and 14, including between the discs. The openings 60 are formed in portions of the hub portion 16d which are between the aforementioned grooves 20. The openings 60 are in the form of slits which are elongated in the axial direction. Where the openings 60 correspond in position with the springs 32, the springs 32 have openings therethrough which correspond to the openings 60.

The second illustrative disc brake system 100 is shown in Figures 2 and 3. The system 100 is identical with the system 10 except as hereinafter explained and like parts are given the same reference numerals as in Figures 2 and 3 and are not described further herein.

The system 100 differs from the system 10 in that, the vanes 62 (only one of which is shown in Figures 2 and 4, and only three of which are shown in Figure 3) are mounted on a phonic wheel 64 which is bolted to a rear surface of the flange 16b. Specifically, the phonic wheel 64 (as shown in Figures 3 and 4) comprises an inner annular portion 64a which is bolted by bolts 66 to the hub portion 16b, a cylindrical connecting portion 64b extending axially from the outer periphery of the portion 64a, and an outer annular portion 64c which is joined at its inner periphery to the connecting portion 64b. As indicated in Figure 3 the annular portion 64c has a plurality of radial slots 66 cut into it, the slots 66 being equally spaced about the axis 18. A tag of metal is bent out through approximately 45° from each slot 66 to form the vanes 62. The vanes 62 also serve the function of acting as pulse creators for a magnetic sensor 68 of an anti-lock braking control system (not shown). As indicated in Figure 2, air can pass through the slots 66 and the openings 60.


## CLAIMS


- 1 A disc brake system (10) comprising a disc (12, 14), and a hub (16) which is arranged to rotate about an axis (18) thereof, the hub comprising a mounting portion (16d) which is generally in the shape of a hollow cylinder, the system also comprising mounting means (20, 22) by which the disc (12, 14) is mounted on the external surface of said mounting portion for rotation with said hub (16) as a unit about said axis (18) and so that the disc can perform axial sliding movement on said hub, characterised in that said hub (16) carries vanes (62) arranged so that, during rotation of the hub (16) about said axis (18), the vanes act to force air into the interior of said mounting portion (16d), and in that said mounting portion (16d) has openings (60) therethrough arranged so that air forced into the interior of the mounting portion (16d) passes through said openings and flows over said disc (12, 14).
- 2 A disc brake system according to claim 1, characterised in that said mounting means (20, 22) comprises a plurality of axially-extending grooves (20) formed in the hub (16) and teeth (22) projecting from the disc into the grooves, each (22) tooth being a sliding fit in one of said grooves (20), said openings (60) being formed in portions of the hub which are between the grooves.
- 3 A disc brake system according to claim 2, characterised in that the system (10) also comprises a plurality of leaf springs (32) mounted on said hub (16) on portions thereof which are between said grooves (20), the leaf springs (32) acting to apply

radial force between the disc (12, 14) and the hub (16), said springs (32) having openings therethrough which correspond to said openings (60) in the hub (16).

- 4 A disc brake system according to any one of claims 1 to 3, characterised in that said vanes (62) are mounted on a phonic wheel (64) mounted on said hub (16).
- 5 A disc brake system according to any one of claims 1 to 4, characterised in that said openings (60) in the hub (16) are in the form of slits which are elongated in the axial direction.


1/4

*Fig. 1*




**Fig. 2**

3/4

*Fig. 3*



4/4

*Fig. 4*

## INTERNATIONAL SEARCH REPORT

International Application No.

PL/GB 99/02533

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 F16D65/847 F16D55/40

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 20150 A (K S TECHNOLOGY HB ;KARLSSON GERTH (SE); SUNDQVIST BENGT (SE)) 5 June 1997 (1997-06-05) abstract; figures 3,4 page 5, line 30 -page 6, line 13 ---	1,2
A	GB 2 164 712 A (AUTOMOTIVE PRODUCTS PLC) 26 March 1986 (1986-03-26) abstract; figures page 2, line 15 - line 44 ---	1,2
A	DE 37 40 373 A (IVECO FIAT ;LORRAINE CARBONE (FR)) 9 June 1988 (1988-06-09) column 3, line 32 - line 65; figure ---	1,2
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 October 1999

Date of mailing of the international search report

27/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3018

Authorized officer

Gertig, I

## INTERNATIONAL SEARCH REPORT

International Application No

PC./GB 99/02533

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 005 676 A (GASSIAT ALAIN L) 9 April 1991 (1991-04-09) abstract; figures column 3, line 25 - line 34 column 4, line 5 - line 22 -----	1,2,5
A	WO 98 26192 A (BUNKER KENNETH JAMES ;T & N TECHNOLOGY LTD (GB)) 18 June 1998 (1998-06-18) cited in the application abstract; figures 1,2 -----	1-3

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02533

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9720150 A	05-06-1997	SE 509044 C AU 7716796 A EP 0864052 A SE 9504286 A	30-11-1998 19-06-1997 16-09-1998 30-05-1997
GB 2164712 A	26-03-1986	NONE	
DE 3740373 A	09-06-1988	IT 1215200 B FR 2607566 A GB 2197924 A,B	31-01-1990 03-06-1988 02-06-1988
US 5005676 A	09-04-1991	FR 2615259 A DE 3866946 A EP 0291429 A JP 1006534 A JP 2661702 B	18-11-1988 30-01-1992 17-11-1988 11-01-1989 08-10-1997
WO 9826192 A	18-06-1998	AU 5404498 A EP 0944780 A GB 2320299 A	03-07-1998 29-09-1999 17-06-1998